

Yanmar Range	Specifications
 <p data-bbox="137 405 296 434"><b>Yanmar 08-1</b></p>	<p data-bbox="384 136 624 165"><b>Excavators SV08-1</b></p> <p data-bbox="384 165 1158 412">Weight 1065 Kg Digging depth 1500 mm Dumping height 1950 mm Rear swing radius 725 mm Engine Yanmar Diesel 2TE67L-BV 7,7 / 10,5 / 2400 (kw/HP/rpm) Digging force (arm/bucket) 650 / 1100 Kgf Travelling speed 2,0 Km/h Transport dimensions (L/W/H) 2600 x 680/840 x 1650/1550 mm</p>
 <p data-bbox="137 629 296 658"><b>Yanmar 15</b></p>	<p data-bbox="384 434 603 463"><b>Excavators SV15</b></p> <p data-bbox="384 463 1230 710">Weight (Cab./Canopy) 1655 / 1535 Kg Digging depth 2000 mm Dumping height 2460 mm Rear swing radius 980 mm Engine Yanmar Diesel 3TNV70-XBVA1 12,1 / 16,5 / 2600 (kw/HP/rpm) Digging force (arm/bucket) 780 / 1400 Kgf Travelling speed 2,0 Km/h Transport dimensions (L/W/H) 3450 x 980 x 2256 mm</p>
 <p data-bbox="137 981 312 1010"><b>Yanmar B25V</b></p>	<p data-bbox="384 712 603 741"><b>Excavators B25V</b></p> <p data-bbox="384 741 1230 987">Weight (Cab./Canopy) 2790 / 2690 Kg Digging depth 2600 mm Dumping height 2700 mm Rear swing radius 1335 mm Engine Yanmar Diesel 3TNV82A-VB1A 15.3 / 20.8 / 2100 (kw/HP/rpm) Digging force (arm/bucket) 1450 / 2040 Kgf Travelling speed 2,5 - 4,5 Km/h Transport dimensions (L/W/H) 4285 x 1468 x 2410 mm</p>
 <p data-bbox="137 1256 312 1285"><b>Yanmar ViO30</b></p>	<p data-bbox="384 1010 612 1039"><b>Excavators ViO30</b></p> <p data-bbox="384 1039 1214 1285">Weight (Cab./Canopy) 3270 / 3140 Kg Digging depth 2800 mm Dumping height 3150 mm Rear swing radius 765 mm Engine Yanmar Diesel 3TNV82A-XBVA 18,4 / 25 / 2500 (kw/HP/rpm) Digging force (arm/bucket) 1800 / 2800 Kgf Travelling speed 2,7 - 4,6 Km/h Transport dimensions (L/W/H) 4325 x 1550 x 2530 mm</p>
 <p data-bbox="137 1576 312 1606"><b>Yanmar ViO55</b></p>	<p data-bbox="384 1308 612 1337"><b>Excavators ViO55</b></p> <p data-bbox="384 1337 1190 1583">Weight (Cab.) 5130 Kg Digging depth 3800 mm Dumping height 4280 mm Rear swing radius 995 mm Engine Yanmar Diesel 4TNV88-XBVA 27,9 / 38 / 2300 (kw/HP/rpm) Digging force (arm/bucket) 2550 / 3800 Kgf Travelling speed 2,3 - 4,5 Km/h Transport dimensions (L/W/H) 5450 x 1990 x 2620 mm</p>
 <p data-bbox="137 1874 312 1904"><b>Yanmar ViO75</b></p>	<p data-bbox="384 1606 612 1635"><b>Excavators ViO75</b></p> <p data-bbox="384 1635 1198 1881">Weight (Cab.) 7720 Kg Digging depth 4200 mm Dumping height 4920 mm Rear swing radius 1130 mm Engine Yanmar Diesel 4TNV98-XBV 43,4 / 58,2 / 2000 (kw/HP/rpm) Digging force (arm/bucket) 3900 / 5590 Kgf Travelling speed 2,7 - 4,7 Km/h Transport dimensions (L/W/H) 6285 x 2270 x 2715 mm</p>

Various attachments such as, augers and peckers (Hydraulic Breakers) are available